

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CA 9800Z ACTIVATOR COMPONENT
Synonym(s) CA 9800Z ACTIVATOR COMPONENT - PRODUCT CODE

1.2 Uses and uses advised against

Use(s) HARDENER

1.3 Details of the supplier of the safety data sheet

Supplier name PPG INDUSTRIES AUSTRALIA PTY. LTD. (ASC - AUSTRALIA)
Address 23 Ovata Drive, Tullamarine, VIC, Australia, 3043
Telephone (03) 9335 1557
Fax (03) 9335 3490
Email contact.aust@ppg.com
Website http://www.ppg.com/coatings/aerospace/

1.4 Emergency telephone number(s)

Emergency 1800 807 001

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classification(s) Flammable Liquids: Category 3
 Skin Sensitisation: Category 1
 Acute Toxicity: Inhalation: Category 4
 Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

2.2 Label elements

Signal word WARNING

Pictograms



Hazard statement(s)

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.

Prevention statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Product name	CA 9800Z ACTIVATOR COMPONENT
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment is advised - see first aid instructions.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use appropriate media for extinction.
Storage statement(s)	
P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS number	EC number	Content
HEXAMETHYLENE DIISOCYANATE, OLIGOMERS	28182-81-2	500-060-2	>60%
3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE, OLIGOMERS	53880-05-0	500-125-5	10 - 30%
N-BUTYL ACETATE	123-86-4	204-658-1	10 - 30%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator where an inhalation risk exists. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitisation by inhalation and skin contact. Individuals with pre-existing respiratory impairment (eg asthmatics) or known sensitivities to isocyanates should avoid exposure.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Flammable. May evolve toxic gases (carbon/ nitrogen oxides, isocyanates, cyanides, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, etc when handling. Earth containers when dispensing fluids.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Product name CA 9800Z ACTIVATOR COMPONENT

5.4 Hazchem code

- 3Y
 - Alcohol Resistant Foam is the preferred firefighting medium. Else use;
 - 3 Normal Foam (protein based foam that is not alcohol resistant).
 - Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Only trained personnel should undertake clean up.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled and protected from physical damage when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems. Store below 35°C.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Substance	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Isocyanates, all (as-NCO)	SWA (AUS)	--	0.02	--	0.07
n-Butyl acetate	SWA (AUS)	150	713	200	950

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Product name CA 9800Z ACTIVATOR COMPONENT

Eye/Face	Wear splash-proof goggles.
Hand	Wear butyl or PVA or viton (R) gloves.
Body	Wear coveralls.
Respiratory	Wear a Type A (Organic vapour) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	CLEAR LIQUID
Odour	SLIGHT ODOUR
Odour Threshold	NOT AVAILABLE
Flammability	FLAMMABLE
Flash Point	28.89°C (cc)
Boiling Point	126.11°C
Melting Point	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE
pH	NOT AVAILABLE
Specific Gravity	1.12
Solubility (water)	INSOLUBLE
Vapour Density	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE

9.2 Other information

No information provided.

Product name **CA 9800Z ACTIVATOR COMPONENT**

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

May polymerise on contact with water or other materials that react with isocyanates.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), alcohols, amines, heat and ignition sources. Reacts with water or moisture, generating carbon dioxide, which may cause container rupture.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides, isocyanates, cyanides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Contact may result in irritation, redness, rash and dermatitis.
Eye	Contact may result in irritation, lacrimation, pain and redness.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	Insufficient data available to classify as a carcinogen.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT - single exposure	Over exposure may result in irritation of the nose and throat, coughing, nausea, dizziness and headache. High level exposure may result in breathing difficulties and unconsciousness.
STOT - repeated exposure	Repeated exposure may damage the respiratory system resulting in irritation of the respiratory tract and lung tissue damage. Repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS), liver and kidney.
Aspiration	Aspiration into the lungs may cause chemical pneumonitis and pulmonary oedema.
Sensitisation	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to low concentrations of isocyanates may cause asthma-like symptoms, including tightness of the chest, coughing, wheezing and shortness of breath.

Product name **CA 9800Z ACTIVATOR COMPONENT**

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

SOIL: If aromatic hydrocarbons are released to soil, they will evaporate from near-surface soil & leach to groundwater. WATER: Biodegradation of aromatics occurs both in soil & groundwater but may be slow. Isocyanates will react with water producing carbon dioxide. ATMOSPHERE: Aromatic hydrocarbons will exist largely as vapour. Half life in atmosphere varies, (eg 1-2 days (xylene); 3 hrs-1 day (toluene)).

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
14.1 UN number	1263	1263	1263
14.2 UN proper shipping name	PAINT or PAINT RELATED MATERIAL		

Product name CA 9800Z ACTIVATOR COMPONENT

14.3 Transport hazard classes

DG Class	3	3	3
Subsidiary risk(s)	None Allocated	-	-

14.4 Packing group

III	III	III
-----	-----	-----

14.5 Environmental hazards

Not a Marine Pollutant

14.6 Special precautions for user

Hazchem Code	•3Y	
EMS		F-E, S-E

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 6 Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications F - Flammable
 Xi - Irritant
 Xn - Harmful

Risk phrases R10: Flammable.
 R20: Harmful by inhalation.
 R37: Irritating to respiratory system.
 R43: May cause sensitisation by skin contact.

Safety phrases S23: Do not breathe gas/fumes/vapour/spray (where applicable).
 S24: Avoid contact with skin.
 S36/37: Wear suitable protective clothing and gloves.
 S45: In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

WHS regulatory information

Ingredient name	CAS number	Regulation	Details
3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE, OLIGOMERS	53880-05-0	Schedule 14 - Health Monitoring	Isocyanates
HEXAMETHYLENE DIISOCYANATE, OLIGOMERS	28182-81-2	Schedule 14 - Health Monitoring	Isocyanates

Inventory listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
 All components are listed on AICS, or are exempt.

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information This product is used in conjunction with other products in the PPG Industries Australia range. Please refer to the appropriate SDS before use.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and

Product name CA 9800Z ACTIVATOR COMPONENT

combustible liquids) for control procedures.

Spillage decontaminants for isocyanates: For TDI or HMDI, use a mixture of sawdust (20%), silica sand (or china clay or Fuller's Earth) (40%) and a breakdown solution (40%). The breakdown solution is made up of water (90%), non-ionic surfactant (2%) and concentrated ammonia (8% v/v). For spillage of any other isocyanate a solid absorbent of silica sand or sawdust may be used.

ISOCYANATES: Asthma sufferers, respiratory impaired or previously sensitised individuals are advised to avoid all exposure to isocyanates. Please note that products containing isocyanates often require the preparation of safe working procedures before product is used.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report Status

This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as

Product name CA 9800Z ACTIVATOR COMPONENT

to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Last Reviewed: 25 Aug 2016

Date Printed: 10 Nov 2016

Based on SDS dated: 14 Aug 2016

End of Report