

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED
Synonym(s) NSN: XXXX-66-160-3789
#17085 - PRODUCT CODE • 66-160-3789 - STOCK NUMBER

1.2 Uses and uses advised against

Use(s) COATING • POLYURETHANE COATING • TWO COMPONENT POLYURETHANE PACK

1.3 Details of the supplier of the safety data sheet

Supplier name PPG INDUSTRIES AUSTRALIA PTY LIMITED
Address 14 McNaughton Rd, Clayton South, VIC, Australia, 3169
Telephone (03) 9263 6000
Fax (03) 9263 6970
Email enquiries@ppg.com
Website <http://www.ppgpmc.com.au>

1.4 Emergency telephone number(s)

Emergency 1800 033 111 (24hr)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classification(s) Flammable Liquids: Category 3
Acute Toxicity: Inhalation: Category 4

2.2 Label elements

Signal word WARNING

Pictograms



Hazard statement(s)

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.

Prevention statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P370 + P378 In case of fire: Use appropriate media for extinction.

Storage statement(s)

P403 + P235 Store in a well-ventilated place. Keep cool.

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS number	EC number	Content
METHYL AMYL KETONE	110-43-0	203-767-1	10 - 30%
2-PENTANONE	107-87-9	203-528-1	<10%
XYLENE	1330-20-7	215-535-7	<10%
BARIUM SULPHATE	7727-43-7	231-784-4	10 - 30%
POLYESTER RESIN	Not Available	Not Available	10 - 30%
PHENOL, 2-[4,6-BIS(2,4-DIMETHYLPHENYL)-1,3,5-TRIAZIN-2-YL]-5-(OCTYLOXY)-, BRANCHED AND LINEAR	195628-73-0	Not Available	<10%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If swallowed or inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Do not give direct mouth-to-mouth resuscitation. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower are recommended.

4.2 Most important symptoms and effects, both acute and delayed

No information provided.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

•3Y

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED

- Alcohol Resistant Foam is the preferred firefighting medium. Else use;
- 3 Normal Foam (protein based foam that is not alcohol resistant).
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation and fire protection systems.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Substance	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Barium sulphate	SWA (AUS)	--	10	--	--
Methyl n-amyl ketone	SWA (AUS)	50	233	--	--
Methyl propyl ketone	SWA (AUS)	200	705	250	881
Xylene	SWA (AUS)	80	--	150	--

Biological limits

Ingredient	Reference	Determinant	Sampling time	BEI
XYLENE	ACGIH BEI	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine

8.2 Exposure controls

Engineering Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED

PPE

- Eye/Face** Wear splash-proof goggles.
- Hand** Wear PVA or viton (R) gloves.
- Body** Wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator or an Air-line respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. Where the boiling point is < 65°C, use an AX filter type.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	RED LIQUID
Odour	SOLVENT ODOUR
Odour Threshold	NOT AVAILABLE
Flammability	FLAMMABLE
Flash Point	23.89°C (cc)
Boiling Point	> 37.78°C
Melting Point	NOT AVAILABLE
Evaporation Rate	< 1 (Butyl acetate = 1)
pH	NOT AVAILABLE
Specific Gravity	0.89
Solubility (water)	INSOLUBLE
Vapour Density	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE

9.2 Other information

% Volatiles	NOT AVAILABLE
--------------------	---------------

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), heat and ignition sources. Incompatible with alkalis (e.g. sodium hydroxide).

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Health Hazard No information provided.

Summary

No information provided.

No information provided.

No information provided.

No information provided.

METHYL AMYL KETONE (110-43-0)

LCLo (Inhalation): 4000 ppm/4 hours (rat)

LD50 (Ingestion): 730 mg/kg (mouse)

LD50 (Intraperitoneal): 400 mg/kg (mouse)

LD50 (Skin): 12.6 ml/kg (rabbit)

2-PENTANONE (107-87-9)

LCLo (Inhalation): 2000 ppm/4 hour (rat)

LD50 (Ingestion): 1600 mg/kg (rat)

LD50 (Intraperitoneal): 800 mg/kg (rat)

LD50 (Skin): 6500 mg/kg (rabbit)

TCLo (Inhalation): 1500 ppm (human)

XYLENE (1330-20-7)

LC50 (Inhalation): 4330–5984 ppm/6 hours (rat)

LCLo (Inhalation): 10000 ppm/6 hours (man)

LD50 (Ingestion): 4300 mg/kg (rat)

LD50 (Intraperitoneal): 1548 mg/kg (mouse)

LD50 (Skin): > 1700 mg/kg (rabbit)

LD50 (Subcutaneous): 1700 mg/kg (rat)

Product name **CA9800/F11136 DESO HS FS#11136 GLOSS RED**

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Wearing the protective equipment outlined, ensure all ignition sources are extinguished. For small quantities, absorb on paper, sand or similar and evaporate under a fume cupboard or open area. For large volumes, atomise into incinerator (mixing with more flammable solvent if required) or recycle by gravimetric separation, distilling & reusing. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
14.1 UN number	1263	1263	1263
14.2 UN proper shipping name	PAINT or PAINT RELATED MATERIAL		
14.3 Transport hazard classes			
DG Class	3	3	3
Subsidiary risk(s)	None Allocated	-	-
14.4 Packing group	III	III	III
14.5 Environmental hazards		None Allocated	
14.6 Special precautions for user			
Hazchem Code	•3Y		
EMS		F-E, S-E	

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Product name	CA9800/F11136 DESO HS FS#11136 GLOSS RED	
Classifications	F - Flammable Xn - Harmful	
Risk phrases	R10:	Flammable.
	R20:	Harmful by inhalation.
Safety phrases	S7:	Keep container tightly closed.
	S9:	Keep container in a well ventilated place.
	S13:	Keep away from food, drink and animal feeding stuffs.
	S23:	Do not breathe gas/fumes/vapour/spray (where applicable).
	S40:	To clean the floor and all objects contaminated by this material use [appropriate material to be specified by the manufacturer].
	S46:	If swallowed, contact a doctor or Poisons Information Centre immediately and show container or label.
	S51:	Use only in well ventilated areas.
	S53:	Avoid exposure - obtain special instructions before use.
	S60:	This material and its container must be disposed of as hazardous waste.
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information This product is used in conjunction with other PPG Industries Coating products. Please refer to the appropriate SDS before use.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

HEALTH EFFECTS FROM EXPOSURE:
It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Product name CA9800/F11136 DESO HS FS#11136 GLOSS RED

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report Status

This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

Prepared By

Risk Management Technologies
 5 Ventnor Ave, West Perth
 Western Australia 6005
 Phone: +61 8 9322 1711
 Fax: +61 8 9322 1794
 Email: info@rmt.com.au
 Web: www.rmt.com.au

Product name **CA9800/F11136 DESO HS FS#11136 GLOSS RED**

Last Reviewed: 10 Oct 2014

Date Printed: 10 Nov 2016

Based on SDS dated: 26 Mar 2012

End of Report