

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name PR 1422 B 2 PART B
Synonym(s) NSN 8030-66-115-1698 • NSN: 8030-01-154-9255 • NSN: 8030-66-126-2127 • PR-1422 B-2, PART B (C161)
FM4100B - PRODUCT CODE (FORMERLY) • PR 1422 B 2 PART B - PRODUCT CODE • PR-1422 B-2 BASE COMPOUND (FORMERLY)

1.2 Uses and uses advised against

Use(s) INDUSTRIAL APPLICATIONS • SEALANT • TWO COMPONENT PACK

1.3 Details of the supplier of the safety data sheet

Supplier name PPG INDUSTRIES AUSTRALIA PTY. LTD. (ASC - AUSTRALIA)
Address 23 Ovata Drive, Tullamarine, VIC, Australia, 3043
Telephone (03) 9335 1557
Fax (03) 9335 3490
Email contact.aust@ppg.com
Website <http://www.ppg.com/coatings/aerospace/>

1.4 Emergency telephone number(s)

Emergency 1800 807 001

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classification(s) Skin Sensitisation: Category 1

2.2 Label elements

Signal word WARNING

Pictograms



Hazard statement(s)

H317 May cause an allergic skin reaction.

Prevention statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P321 Specific treatment is advised - see first aid instructions.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS number	EC number	Content
------------	------------	-----------	---------

Product name **PR 1422 B 2 PART B**

Ingredient	CAS number	EC number	Content
CALCIUM CARBONATE	471-34-1	207-439-9	10 - <30%
EPOXY RESIN AND BISPHENOL A POLYMER	25036-25-3	607-500-3	1 - <10%
TOLUENE	108-88-3	203-625-9	1 - <10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	remainder
HYDROGENATED TERPHENYLS	61788-32-7	262-967-7	1 - <10%

4. FIRST AID MEASURES

No information provided.

No information provided.

Treat symptomatically.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

No information provided.

5.2 Special hazards arising from the substance or mixture

No information provided.

5.3 Advice for firefighters

No information provided.

5.4 Hazchem code

None allocated

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

No information provided.

6.2 Environmental precautions

No information provided.

6.3 Methods of cleaning up

No information provided.

6.4 Reference to other sections

No information provided.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

No information provided.

7.2 Conditions for safe storage, including any incompatibilities

No information provided.

7.3 Specific end use(s)

No information provided.

Product name **PR 1422 B 2 PART B**

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Substance	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Calcium carbonate (Limestone, Marble, Whiting)	SWA (AUS)	--	10	--	--
Hydrogenated terphenyls	SWA (AUS)	0.5	4.9	--	--
Toluene	SWA (AUS)	50	191	150	574

Biological limits

Ingredient	Reference	Determinant	Sampling time	BEI
TOLUENE	ACGIH BEI	o-Cresol in urine	End of shift	0.02 mg/L
	ACGIH BEI	Toluene in urine	End of shift	0.03 mg/L
	ACGIH BEI	Toluene in blood	Prior to last shift of workweek	0.02 mg/L

8.2 Exposure controls

Engineering Controls No information provided.

PPE

Eye/Face Wear splash-proof goggles.

Hand Wear butyl or PVA or viton (R) gloves.

Body Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.

Respiratory Wear a Type AB (Organic and Inorganic gases/vapours) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	BROWN SOLID
Odour	SLIGHT ODOUR
Odour Threshold	NOT AVAILABLE
pH	NOT AVAILABLE
Melting Point	NOT AVAILABLE
Boiling Point	NOT AVAILABLE
Flash Point	70°C (cc)
Evaporation Rate	NOT AVAILABLE
Flammability	COMBUSTIBLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	1.3 %
Vapour Pressure	NOT AVAILABLE
Vapour Density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE

Product name	PR 1422 B 2 PART B
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE
Specific Gravity	1.38

9.2 Other information

No information provided.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information in sections 10.2 to 10.6.

10.2 Chemical stability

No information provided.

10.3 Possibility of hazardous reactions

No information provided.

10.4 Conditions to avoid

No information provided.

10.5 Incompatible materials

No information provided.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Health hazard summary	Harmful - irritant. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. Repeated exposure to organic solvents may result in liver, kidney and CNS damage. May cause sensitisation by skin contact.
Eye	Irritant. Contact may result in irritation, lacrimation, pain and redness.
Inhalation	Harmful - irritant. Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness. Repeated exposure to some solvents may result in liver, kidney and central nervous system (CNS) damage.
Skin	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis. May be absorbed through skin with harmful effects. May cause sensitisation by skin contact.
Ingestion	Harmful. Ingestion may result in nausea, vomiting, abdominal pain, dizziness, fatigue and diarrhoea. Ingestion of large quantities may result in liver and kidney damage, and unconsciousness. Aspiration or inhalation may cause chemical pneumonitis and pulmonary oedema.
Toxicity data	<p>CALCIUM CARBONATE (471-34-1) LD50 (Ingestion): 6450 mg/kg (rat)</p> <p>EPOXY RESIN AND BISPHENOL A POLYMER (25036-25-3) LD50 (Ingestion): 2-19 g/kg (rat)</p> <p>TOLUENE (108-88-3) LC50 (Inhalation): 400 ppm/24 hours (mouse) LCLo (Inhalation): 1600 ppm (guinea pig) LD50 (Ingestion): 636 mg/kg (rat) LD50 (Skin): 14100 µL/kg (rabbit) LDLo (Ingestion): 50 mg/kg (human)</p> <p>HYDROGENATED TERPHENYLS (61788-32-7) LD50 (Ingestion): 12.5 g/kg (mouse)</p>

Product name **PR 1422 B 2 PART B**

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

No information provided.

Legislation

Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
14.1 UN number	None Allocated	None Allocated	None Allocated
14.2 UN proper shipping name	None Allocated	None Allocated	None Allocated
14.3 Transport hazard classes			
DG Class	None Allocated	None Allocated	None Allocated
Subsidiary risk(s)	None Allocated	None Allocated	None Allocated
14.4 Packing group	None Allocated	None Allocated	None Allocated
14.5 Environmental hazards		None Allocated	
14.6 Special precautions for user			
Hazchem Code	None Allocated		

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	Xi - Irritant	
Risk phrases	R43:	May cause sensitisation by skin contact.
Safety phrases	S24:	Avoid contact with skin.
	S37:	Wear suitable gloves.
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

Product name PR 1422 B 2 PART B

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

HEALTH EFFECTS FROM EXPOSURE:
It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m ³	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)

Product name PR 1422 B 2 PART B

SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report Status This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Last Reviewed: 30 Mar 2016

Date Printed: 20 Oct 2016

Based on SDS dated: 28 Sep 2015

End of Report