

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name 635 RETAINING COMPOUND SLIP FIT
Synonym(s) 135516 - IDH NUMBER • 635 RETAINING COMPOUND (FORMERLY) • 63531 - ITEM NUMBER • LOCTITE 635 RETAINING COMPOUND SLIP FIT • SLIP FIT RETAINING COMPOUND

1.2 Uses and uses advised against

Use(s) ADHESIVE • ANAEROBIC ADHESIVE • RETAINING COMPOUND

1.3 Details of the supplier of the safety data sheet

Supplier name HENKEL AUSTRALIA PTY LTD
Address 135 - 141 Canterbury Road, Kilsyth, Victoria, Australia, 3137
Telephone (03) 9724 6444
Fax (03) 9728 5877
Email msds@au.henkel.com
Website <http://www.loctite.com.au>

1.4 Emergency telephone number(s)

Emergency 1800 032 379; (03) 9724 6556

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classification(s) Skin Corrosion/Irritation: Category 2
Skin Sensitization: Category 1
Serious Eye Damage / Eye Irritation: Category 2A
Specific Target Organ Systemic Toxicity (Single Exposure): Category 3
Aquatic Toxicity (Chronic): Category 3

2.2 Label elements

Signal word

WARNING

Pictograms



Hazard statement(s)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Prevention statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment. This statement does not apply where this is the intended use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Product name	635 RETAINING COMPOUND SLIP FIT
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment is advised - see first aid instructions.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before re-use.
Storage statement(s)	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed (applies if the substance is volatile so as to generate a hazardous atmosphere).
P405	Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS number	EC number	Content
ACRYLIC ACID	79-10-7	201-177-9	<10%
CUMENE HYDROPEROXIDE	80-15-9	201-254-7	<5%
METHACRYLIC ACID	79-41-4	201-204-4	<5%
TRIETHYLENE GLYCOL DIMETHACRYLATE	109-16-0	203-652-6	<5%
HYDROXYPROPYL METHACRYLATE	27813-02-1	248-666-3	30-60%
RESIN(S)	Not Available	Not Available	20-60%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	remainder

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

No information provided.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve carbon oxides and hydrocarbons when heated to decomposition. May evolve nitrogen oxides when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Product name 635 RETAINING COMPOUND SLIP FIT

5.4 Hazchem code

None allocated

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Only trained personnel should undertake clean up.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems. Store as a Class C1 Combustible Liquid (AS1940). Store below 38°C.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Substance	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Acrylic acid	SWA (AUS)	2	5.9	--	--
Methacrylic acid	SWA (AUS)	20	70	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

- Eye/Face** Wear splash-proof goggles.
- Hand** Wear butyl or nitrile gloves.
- Body** Wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Product name 635 RETAINING COMPOUND SLIP FIT

9.1 Information on basic physical and chemical properties

Appearance	GREEN LIQUID
Odour	SHARP IRRITATING ODOUR
Odour Threshold	NOT AVAILABLE
pH	NOT AVAILABLE
Melting Point	NOT AVAILABLE
Boiling Point	> 149°C
Flash Point	> 93°C (cc)
Evaporation Rate	NOT AVAILABLE
Flammability	CLASS C1 COMBUSTIBLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	NOT AVAILABLE
Vapour Pressure	< 10 mm Hg
Vapour Density	NOT AVAILABLE
Solubility (water)	SLIGHTLY SOLUBLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE
Specific Gravity	1.09

9.2 Other information

% Volatiles	NOT AVAILABLE
Density	1.1 g/cm ³

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

May polymerise with violent rupture/explosion.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

May polymerise in contact with oxidising agents (e.g. nitrates), acids (e.g. nitric acid), amines, UV light, alkalis (e.g. sodium hydroxide), or if heated. Polymerisation may generate heat with potential for fire-explosion.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

Product name 635 RETAINING COMPOUND SLIP FIT

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Health hazard summary	Harmful - irritant. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact.
Eye	Irritant. Contact may result in irritation, lacrimation, pain and redness. May result in burns with prolonged contact.
Inhalation	Irritant. Over exposure may result in mucous membrane irritation of the respiratory tract, coughing, weakness, nausea, vomiting and headache. High level exposure may result in dizziness, drowsiness, respiratory tract inflammation and breathing difficulties.
Skin	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis. May be absorbed through skin with harmful effects. May cause sensitisation by skin contact.
Ingestion	Harmful. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness. Aspiration or inhalation may cause chemical pneumonitis and pulmonary oedema.
Toxicity data	ACRYLIC ACID (79-10-7) LC50 (Inhalation): 5300 mg/m ³ /2 hours (mouse) LCLo (Inhalation): 4000 ppm/4 hours (rat) LD50 (Ingestion): 250 mg/kg (rat) LD50 (Intraperitoneal): 22 mg/kg (rat) LD50 (Skin): 280 mg/kg (rabbit) LD50 (Subcutaneous): 1590 mg/kg (mouse) TDLo (Ingestion): 100 g/kg (rat) CUMENE HYDROPEROXIDE (80-15-9) LC50 (Inhalation): 200 ppm/4 hours (mouse) LD50 (Ingestion): 382 mg/kg (rat) LD50 (Intraperitoneal): 95 mg/kg (rat) LD50 (Skin): 500 mg/kg (rat) LD50 (Subcutaneous): 392 mg/kg (rat) LDLo (Ingestion): 5000 mg/kg (mouse) LDLo (Skin): 1200 mg/kg (rabbit) METHACRYLIC ACID (79-41-4) LD50 (Ingestion): 1060 mg/kg (rat) LD50 (Intraperitoneal): 48 mg/kg (mouse) LD50 (Skin): 1 g/kg (Guinea pig) TCLo (Inhalation): 221 mg/m ³ /24 hour/17 weeks-continuous (rat) TDLo (Ingestion): 910 mg/kg/26 weeks-intermittent (rat) TRIETHYLENE GLYCOL DIMETHACRYLATE (109-16-0) LD50 (Ingestion): 10750 mg/kg (mouse)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

No information provided.

Product name **635 RETAINING COMPOUND SLIP FIT**

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
14.1 UN number	None Allocated	None Allocated	None Allocated
14.2 UN proper shipping name	None Allocated	None Allocated	None Allocated
14.3 Transport hazard classes			
DG Class	None Allocated	None Allocated	None Allocated
Subsidiary risk(s)	None Allocated	None Allocated	None Allocated
14.4 Packing group	None Allocated	None Allocated	None Allocated
14.5 Environmental hazards		None Allocated	
14.6 Special precautions for user			
Hazchem Code	None Allocated		

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications N - Dangerous for the environment
Xi - Irritant

Risk phrases R36/37/38: Irritating to eyes, respiratory system and skin.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases S24/25: Avoid contact with skin and eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28: After contact with skin, wash immediately with plenty of water.
S37/39: Wear suitable gloves and eye/face protection.
S61: Avoid release to the environment. Refer to special instructions/safety data sheets.

Inventory listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
All components are listed on AICS, or are exempt.

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information **WORKPLACE CONTROLS AND PRACTICES:** Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

Product name **635 RETAINING COMPOUND SLIP FIT**

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

HEALTH EFFECTS FROM EXPOSURE:
It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all ChemAlert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all ChemAlert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report Status

This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

Product name **635 RETAINING COMPOUND SLIP FIT**

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Last Reviewed: 20 Jan 2015

Date Printed: 06 Mar 2015

Based on SDS dated: 02 Nov 2012

End of Report