

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** KWIK GRIP (PRODUCT OBSOLETE)  
**Synonym(s)** NSN: 8040-66-023-4688 • NSN: 8040-66-150-1279 • NSN: 8040-66-150-1280 • NSN: 8040-66-150-1281 • NSN: 8040-66-150-1282 • NSN: 8040-66-150-1283  
000700612501 - SUBSTANCE NUMBER • 100043, 930069710227001, 100041, 100089, 930069712132501 - PRODUCT CODE • 930069710117403, 100039, 100044, 9300697118936 - PRODUCT CODE • SELLEYS KWIK GRIP • SOLVENT BORNE POLYCHLOROPRENE/RESIN BASED ADHESIVE

### 1.2 Uses and uses advised against

**Use(s)** ADHESIVE • BONDING AGENT

### 1.3 Details of the supplier of the safety data sheet

**Supplier name** SELLEYS PTY LIMITED  
**Address** 1 Gow St, Padstow, NSW, Australia, 2211  
**Telephone** 1300 555 205 (Australia), 9820 4852 (New Zealand)  
**Fax** 1300 555 305 (Australia), 0800 804 583 (New Zealand)  
**Email** selleys.customer.service@selleys.com.au  
**Website** <http://www.selleys.com.au>

### 1.4 Emergency telephone number(s)

**Emergency** 1800 033 111

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**GHS Classification(s)** Flammable Liquids: Category 2  
Aspiration Hazard: Category 1  
Skin Corrosion/Irritation: Category 2  
Specific Target Organ Systemic Toxicity (Single Exposure): Category 3  
Toxic to Reproduction: Category 2  
Specific Target Organ Systemic Toxicity (Repeated Exposure): Category 2

### 2.2 Label elements

**Signal word**

**DANGER**

**Pictograms**



**Hazard statement(s)**

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.

**Prevention statement(s)**

P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P243 Take precautionary measures against static discharge.

<b>Product name</b>	<b>KWIK GRIP (PRODUCT OBSOLETE)</b>
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
<b>Response statement(s)</b>	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P321	Specific treatment is advised - see first aid instructions.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P370 + P378	In case of fire: Use appropriate media for extinction (applies if water increases risk).
<b>Storage statement(s)</b>	
P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up.
<b>Disposal statement(s)</b>	
P501	Dispose of contents/container in accordance with relevant regulations.

**2.3 Other Hazards**

No information provided.

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

**3.1 Substances / Mixtures**

Ingredient	CAS number	EC number	Content
TOLUENE	108-88-3	203-625-9	30-60%
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	64742-49-0	265-151-9	10-30%
METHYL ETHYL KETONE (MEK)	78-93-3	201-159-0	1-10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	remainder

**4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>First aid facilities</b>	No information provided.

**4.2 Most important symptoms and effects, both acute and delayed**

Acute: Irritating to the skin. Vapours may cause drowsiness and dizziness. Chronic: Central nervous system (CNS), liver and kidney damage. Possible risk of harm to the unborn child.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

**Product name** KWIK GRIP (PRODUCT OBSOLETE)

**5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

**5.2 Special hazards arising from the substance or mixture**

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights and mobile phones when handling. Earth containers when dispensing fluids.

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

- 3YE
  - Alcohol resistant foam is the preferred firefighting medium
  - 3 Foam
  - Y Self Contained Breathing apparatus and protective gloves.
  - E Evacuation of people in the vicinity of the incident should be considered.

**6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

**7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation and fire protection systems.

**7.3 Specific end use(s)**

No information provided.

**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION**

**8.1 Control parameters**

**Exposure standards**

Substance	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Methyl ethyl ketone (MEK)	SWA (AUS)	150	445	300	890
Mineral Oil Mist	SWA (AUS)	--	5	--	--
Toluene	SWA (AUS)	50	191	150	574

**Product name** KWIK GRIP (PRODUCT OBSOLETE)

**Biological limits**

Ingredient	Reference	Determinant	Sampling time	BEI
METHYL ETHYL KETONE (MEK)	ACGIH BEI	MEK in urine	End of shift	2 mg/L
TOLUENE	ACGIH BEI	o-Cresol in urine	End of shift	0.02 mg/L
	ACGIH BEI	Toluene in urine	End of shift	0.03 mg/L
	ACGIH BEI	Toluene in blood	Prior to last shift of workweek	0.02 mg/L

**8.2 Exposure controls**

**Engineering Controls**

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/ explosive vapours may accumulate in poorly ventilated areas. Vapours may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

**PPE**

**Eye/Face**

Wear splash-proof goggles.

**Hand**

Wear PVA or viton (R) gloves.

**Body**

Wear coveralls.

**Respiratory**

Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. At high vapour levels, wear an Air-line respirator. If using product in a confined area, wear Self Contained Breathing Apparatus (SCBA).



**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	VISCOUS YELLOW LIQUID
<b>Odour</b>	SOLVENT ODOUR
<b>Odour Threshold</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Melting Point</b>	NOT AVAILABLE
<b>Boiling Point</b>	95°C (Approximately)
<b>Flash Point</b>	-5°C
<b>Evaporation Rate</b>	NOT AVAILABLE
<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Upper Explosion Limit</b>	7.1 % (Toluene)
<b>Lower Explosion Limit</b>	1.2 % (Toluene)
<b>Vapour Pressure</b>	7.3 kPa @ 20°C
<b>Vapour Density</b>	> 1 (Air = 1)
<b>Solubility (water)</b>	INSOLUBLE
<b>Partition Coefficient</b>	NOT AVAILABLE
<b>Autoignition Temperature</b>	NOT AVAILABLE
<b>Decomposition Temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	2.5 Pa/sec
<b>Explosive Properties</b>	NOT AVAILABLE
<b>Oxidising Properties</b>	NOT AVAILABLE
<b>Specific Gravity</b>	0.95 (Approximately)

**9.2 Other information**

**% Volatiles** 75 %

**Product name**                    **KWIK GRIP (PRODUCT OBSOLETE)**

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization is not expected to occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), heat and ignition sources.

**10.6 Hazardous decomposition products**

May evolve carbon oxides and hydrocarbons when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

<b>Health hazard summary</b>	Harmful - irritant. This product has the potential to cause adverse health effects. Use safe work practices to avoid eye or skin contact and inhalation. Chronic exposure may result in central nervous system (CNS), liver and kidney damage. Possible risk of harm to the unborn child.
<b>Eye</b>	Irritant. Contact may result in irritation, lacrimation, pain and redness. May result in burns with prolonged contact.
<b>Inhalation</b>	Harmful - irritant. Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness. Chronic exposure may result in liver, kidney and CNS damage. Possible risk of harm to the unborn child.
<b>Skin</b>	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis. May be absorbed through skin with harmful effects.
<b>Ingestion</b>	Harmful. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness. Chronic exposure may result in central nervous system (CNS), liver and kidney damage. Aspiration or inhalation may cause chemical pneumonitis and pulmonary oedema.
<b>Toxicity data</b>	<p>TOLUENE (108-88-3)</p> <p>LC50 (Inhalation): 400 ppm/24 hours (mouse)</p> <p>LCLo (Inhalation): 1600 ppm (guinea pig)</p> <p>LD50 (Ingestion): 636 mg/kg (rat)</p> <p>LD50 (Skin): 14100 µL/kg (rabbit)</p> <p>LDLo (Ingestion): 50 mg/kg (human)</p> <p>METHYL ETHYL KETONE (MEK) (78-93-3)</p> <p>LC50 (Inhalation): 23500 mg/kg (rat)</p> <p>LD50 (Ingestion): 2737 mg/kg (rat)</p> <p>LD50 (Intraperitoneal): 607 mg/kg (rat)</p> <p>LD50 (Skin): 6480 mg/kg (rabbit)</p> <p>TCLo (Inhalation): 100 ppm/5 minutes (Human - eye irritant)</p>

Product name **KWIK GRIP (PRODUCT OBSOLETE)**

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

No information provided.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Results of PBT and vPvB assessment**

No information provided.

**12.6 Other adverse effects**

If aromatic hydrocarbons are released to soil, they will evaporate from near-surface soil & leach to groundwater. Biodegradation occurs in soil & groundwater but may be slow, especially at high concentrations, which can be toxic to microorganisms. Will exist largely as vapour in air. Half life in atmosphere depends on particular hydrocarbon (eg 1-2 days (xylene); 3 hrs-1 day (toluene)).

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Waste disposal** Wearing the protective equipment outlined, ensure all ignition sources are extinguished. For small quantities, absorb on paper, sand or similar and evaporate under a fume cupboard or open area. For large volumes, atomise into incinerator (mixing with more flammable solvent if required) or recycle by gravimetric separation, distilling & reusing. Contact the manufacturer/supplier for additional information (if required).

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
<b>14.1 UN number</b>	1133	1133	1133
<b>14.2 UN proper shipping name</b>		ADHESIVES containing flammable liquid	
<b>14.3 Transport hazard classes</b>			
<b>DG Class</b>	3	3	3
<b>Subsidiary risk(s)</b>	None Allocated	-	-
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>		None Allocated	
<b>14.6 Special precautions for user</b>			
<b>Hazchem Code</b>	●3YE		
<b>EMS</b>		F-E, S-D	

**15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** Classified as a Schedule 5 Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications**

<b>Product name</b>	<b>KWIK GRIP (PRODUCT OBSOLETE)</b>	
	F - Highly flammable Repr. - Reproductive toxin Xi - Irritant Xn - Harmful	
<b>Risk phrases</b>	R11:	Highly flammable.
	R38:	Irritating to skin.
	R48/20:	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	R63:	Possible risk of harm to the unborn child.
	R65:	Harmful: May cause lung damage if swallowed.
	R67:	Vapours may cause drowsiness and dizziness.
<b>Safety phrases</b>	S16:	Keep away from sources of ignition - No smoking.
	S24/25:	Avoid contact with skin and eyes.
	S29:	Do not empty into drains.
	S33:	Take precautionary measures against static discharges.
	S36/37/39:	Wear suitable protective clothing, gloves and eye/face protection.
	S38:	In case of insufficient ventilation, wear suitable respiratory equipment.
	S45:	In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).
<b>Inventory listing(s)</b>	<b>AUSTRALIA: AICS (Australian Inventory of Chemical Substances)</b> All components are listed on AICS, or are exempt.	

**15.2 Chemical safety assessment**

No information provided.

**16. OTHER INFORMATION**

**Additional information** RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

HEALTH EFFECTS FROM EXPOSURE:  
It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:  
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all ChemAlert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all ChemAlert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a

**Product name**                    **KWIK GRIP (PRODUCT OBSOLETE)**

moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report Status**

This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

**Prepared By**

Risk Management Technologies  
 5 Ventnor Ave, West Perth  
 Western Australia 6005  
 Phone: +61 8 9322 1711  
 Fax: +61 8 9322 1794  
 Email: info@rmt.com.au  
 Web: www.rmt.com.au



**Product name**            **KWIK GRIP (PRODUCT OBSOLETE)**

**Last Reviewed:** 28 Jan 2015

**Date Printed:** 06 Mar 2015

**Based on SDS dated:** 13 Jan 2015

**End of Report**