

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B
Synonym(s) NSN: 8040-00-463-7042
 EA 956 SYSTEM PART B • HENKEL HYSOL EA 956 SYSTEM PART B • HYSOL EA 956 SYSTEM PART B (FORMERLY)

1.2 Uses and uses advised against

Use(s) ADHESIVE • AEROSPACE APPLICATIONS • EPOXY RESIN SYSTEM • TWO COMPONENT EPOXY SYSTEM

1.3 Details of the supplier of the safety data sheet

Supplier name HENKEL AUSTRALIA PTY LTD
Address 135 - 141 Canterbury Road, Kilsyth, Victoria, Australia, 3137
Telephone (03) 9724 6444
Fax (03) 9728 5877
Email msds@au.henkel.com
Website http://www.loctite.com.au

1.4 Emergency telephone number(s)

Emergency 1800 032 379; (03) 9724 6556

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classification(s) Acute Toxicity: Oral: Category 4
 Acute Toxicity: Skin: Category 4
 Skin Corrosion/Irritation: Category 1B
 Skin Sensitization: Category 1
 Serious Eye Damage / Eye Irritation: Category 1

2.2 Label elements

Signal word DANGER

Pictograms



Hazard statement(s)

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

Prevention statement(s)

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Product name	LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
Storage statement(s)	
P405	Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS number	EC number	Content
DIETHYLENETRIAMINE	111-40-0	203-865-4	10-30%
TRIETHYLENETETRAMINE (TETA)	112-24-3	203-950-6	<5%
AMINE ADDUCT	Not Available	Not Available	>60%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

No information provided.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve toxic gases (carbon/ nitrogen oxides, amines, ammonia, hydrocarbons) when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2X

Product name LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B

- 2 Water Fog (or fine water spray if fog unavailable)
- X Full protective clothing including Self Contained Breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation systems. Store as a Class C1 Combustible Liquid (AS1940). Avoid mixing batches greater than 450 grams as excessive heat build-up can occur which may result in the release of toxic gases. Do not heat mixed adhesive above 52°C unless curing surfaces to be bonded.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Substance	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Diethylene triamine	SWA (AUS)	1	4.2	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

- Eye/Face** Wear splash-proof goggles.
- Hand** Wear butyl or viton (R) gloves.
- Body** Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.
- Respiratory** Wear a Type A (Organic vapour) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Product name LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B

9.1 Information on basic physical and chemical properties

Appearance	AMBER COLOURED LIQUID
Odour	AMMONIACAL ODOUR
Odour Threshold	NOT AVAILABLE
pH	ALKALINE
Melting Point	NOT AVAILABLE
Boiling Point	NOT AVAILABLE
Flash Point	> 60.5°C
Evaporation Rate	NOT AVAILABLE
Flammability	CLASS C1 COMBUSTIBLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE
Vapour Density	NOT AVAILABLE
Solubility (water)	SOLUBLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE
Specific Gravity	0.96

9.2 Other information

% Volatiles NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides, amines, ammonia, hydrocarbons) when heated to decomposition.

Product name **LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B**

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Health hazard summary	Corrosive. This product has the potential to cause adverse health effects. Use safe work practices to avoid eye or skin contact and inhalation. Potential sensitising agent. Individuals with pre-existing respiratory impairment (eg asthmatics) or skin sensitivities may be more susceptible to adverse health effects.
Eye	Corrosive. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Inhalation	Slightly corrosive - irritant. Over exposure may result in irritation of the nose and throat, with coughing. May cause sensitisation by inhalation. High level exposure may result in breathing difficulties, ulceration, pulmonary oedema and unconsciousness.
Skin	Slightly corrosive. Contact may result in irritation, redness, pain, rash, dermatitis and possible burns. May cause sensitisation by skin contact. May be absorbed through skin with harmful effects.
Ingestion	Highly corrosive - toxic. Ingestion may result in burns to the mouth and throat, nausea, vomiting, ulceration of the gastrointestinal tract, oedema, rapid pulse, shock, unconsciousness, convulsions and death.
Toxicity data	<p>DIETHYLENETRIAMINE (111-40-0)</p> <p>LD50 (Ingestion): 1080 mg/kg (rat)</p> <p>LD50 (Intraperitoneal): 71 mg/kg (mouse)</p> <p>LD50 (Skin): 0.17 mL/kg (guinea pig)</p> <p>TDLo (Ingestion): 1820 mg/kg/26 weeks intermittently (rabbit)</p> <p>TRIETHYLENETETRAMINE (TETA) (112-24-3)</p> <p>LD50 (Ingestion): 1600 mg/kg (mouse)</p> <p>LD50 (Intraperitoneal): 468 mg/kg (mouse)</p> <p>LD50 (Intravenous): 350 mg/kg (mouse)</p> <p>LD50 (Skin): 805 mg/kg (rabbit)</p>

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Product name **LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B**



	Land Transport (ADG)	Sea Transport (IMDG/IMO)	Air Transport (IATA/ICAO)
14.1 UN number	2735	2735	2735
14.2 UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.		
14.3 Transport hazard classes			
DG Class	8	8	8
Subsidiary risk(s)	None Allocated	-	-
14.4 Packing group	II	II	II
14.5 Environmental hazards		None Allocated	
14.6 Special precautions for user			
Hazchem Code	2X		
EMS		F-A, S-B	

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	C - Corrosive Xi - Irritant Xn - Harmful	
Risk phrases	R21/22:	Harmful in contact with skin and if swallowed.
	R34:	Causes burns.
	R41:	Risk of serious damage to eyes.
	R43:	May cause sensitisation by skin contact.
Safety phrases	S23:	Do not breathe gas/fumes/vapour/spray (where applicable).
	S26:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
	S27:	Take off immediately all contaminated clothing.
	S28:	After contact with skin, wash immediately with plenty of water.
	S36/37/39:	Wear suitable protective clothing, gloves and eye/face protection.
	S45:	In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information This product is used in conjunction with HYSOL EA 956 SYSTEM PART A. Please refer to the appropriate SDS before use.

SYNERGISM - ANTAGONISM: Ingredients in this product may act together to aggravate or reduce adverse effects. Accordingly the Exposure Standard provided for single ingredients should be considered as a guide only and all due care exercised when handling.

Product name

LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

HEALTH EFFECTS FROM EXPOSURE:
It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all ChemAlert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all ChemAlert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons

Product name LOCTITE EA 956 PART B KNOWN AS HYSOL EA 956 SYSTEM PART B

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Report Status This ChemAlert report has been independently compiled by RMT's scientific department utilising the original Safety Data Sheet ('SDS') for the product provided to RMT by the manufacturer. The information is based on the latest chemical and toxicological research and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. It is an independent collation by RMT of information obtained from the original SDS for this product. Its content has not been authorised or verified by the manufacturer / distributor of the chemical to which it relates.

This ChemAlert report does not constitute the manufacturer's original SDS and is not intended to be a replacement for same. It is provided to subscribers of ChemAlert as a reference tool only, is not all-inclusive and does not represent any guarantee as to the properties of the product. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this ChemAlert report, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this ChemAlert report.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Last Reviewed: 20 Feb 2015

Date Printed: 16 Mar 2015

Based on SDS dated: 21 May 2014

End of Report